

## RUST F2 V

NON SMOKE SOLVENT FOR THE REMOVAL OF THE OXIDATIONS FROM THE METALLIC SURFACES.

### USE:

**RUST F2 V** is specially designed for a complete removal of rust and oxidation. Applied with a brush or spray, **RUST F2 V** adheres without scrolling even on vertical surfaces, simultaneously penetrates grease and removes sludge, rust and oxidation. The metal surface if of steel, is made glossy and free of rust spots (pitting of steel) if iron or aluminium, is made porous to improve the anchoring of the protective layer and at the same time is protected against a fast reform of oxide until it cannot be covered with a suitable protective coating.

### ADVANTAGES:

- High active:

Unlike other deoxidizers **RUST F2 V**, with an only application, it penetrates in depth through the fats and various layers of dirt without the need of preliminary cleaning or degreasing operations. **RUST F2 V** remove the rust and the corrosion, and it makes the surfaces slightly porous for a greater anchorage for a possible painting.

- Safe:

**RUST F2 V** doesn't absolutely damage surfaces in steel or in aluminium. It is sure since it is not irritant in case of a short contact with the skin and it doesn't produce dangerous smokes.

- Cheap:

Its particularly formulation reduces the cost of labour. The high concentration of its components allows a dilution of our chemical speciality with three parts of water to be used in immersion.

### SUGGESTIONS FOR USE:

On the ferrous materials: remove previously the rust and the dirt with a brush. Apply **RUST F2 V** with a sprayer and to leave to react for about 30 or 60

minutes. If the surfaces will not be immediately protected, don't rinse out with water. RUST F2 V gives to the treated surface a temporary protection.

On the steel or on aluminium in presence of light oxidations, RUST F2 V can be diluted with water up to the range of 1 to 1 and applied with a sprayer. Leave the solution on the surface for almost **30 or 60 minutes**. At the end of the operation rinse out with water or with a moist sponge. If it is necessary, repeat the treatment for the most tenacious deposits.

**(CAUTION do not apply on anodized aluminium or galvanized surfaces).**

### **CHARACTERISTICS COD. 51A30**

Kind of product:	-	Non smoke chemical based on solvent for the removal of the oxidations.
Colour	-	Red
Smell	-	Sweet
Viscosity Centipoise	-	F1-75 F2-700
Flammability	-	Flameproof
Toxicity	-	Low, harmful if ingested
Composition	-	Smokeless acids agents for the removal of rust, with addition of compatible organic solvents.

NOTE: - The contents of this document is based on our own knowledge and experience on the product. It's given as an indication, do not assume our responsibility for particular applications.